

Compensation & Extension Cables

PVC insulated cables

A 9 L · A 9-100 L · A 9-075 L · A 9-050 L · A 9-022 L

also available as
halogen-free
construction



A 9 L · A 9-100 L · A 9-075 L · A 9-050 L



A 9-022L

Construction:

Insulation:	PVC, Tl2 acc. to EN 50363-3 + VDE 0207-363-3
Stranding:	2 conductors together
Jacket material:	PVC, TM2 acc. to EN 50363-4-1 + VDE 0207-363-4-1
Shape:	round
Conductor construction:	strand

Technical data:

Min. bending radius:	7.5 x O.D.
Radiation resistance:	8 x 10 ⁷ cJ/kg
Temperature range of insulation:	static: -40/+70°C flexible: +5/+70°C
Insulation resistance:	> 1MΩ x km
Burning characteristics:	flame retardant and self-extinguishing acc. to IEC 60332-1-2 + VDE 0482-332-1-2
Absence of harmful substances:	acc. to RoHS directive of the European Union see page O/30

Type: Conductor cross section: Outer diameter: Weight/100m:	A 9 L: 1.5 mm ² approx. 6.1 mm approx. 5.0 kg	A 9-100 L: 1.0 mm ² approx. 5.1 mm approx. 4.4 kg	A 9-075 L: 0.75 mm ² approx. 4.9 mm approx. 3.9 kg	A 9-050 L: 0.50 mm ² approx. 4.3 mm approx. 2.9 kg	A 9-022 L: 0.22 mm ² approx. 3.3 mm approx. 1.6 kg
---	--	--	---	---	---

IEC 60584

for thermocouple	EMK at 100°C in mV	cable type	A 9 L item no.	A 9-100 L item no.	A 9-075 L item no.	A 9-050 L item no.	A 9-022 L item no.
Type T	4.28	TX	4428958	4426958	4425958	4423958	4501958
Type J	5.27	JX	4428952	4426952	4425952	4423952	4501952
Type K	4.10	KCA	4428995	4426995	4425995	4423995	4501995
Type K	4.10	KCB	4428999	4426999	4425999	4423999	4501999
Type K	4.10	KX	4428954	4426954	4425954	4423954	4501954
Type E	6.32	EX	4428953	4426953	4425953	4423953	4501953
Type R/S	0.65	R/SCB	4428997	4426997	4425997	4423997	4501997
Type N	2.77	NC	4428991	4426991	4425991	4423991	4501991

DIN 43710 / 43714 (not valid for type B*)

We continue to manufacture compensating and extension cables with color code acc. to DIN 43714 and the basic values of DIN 43710.

for thermocouple	EMK at 100°C in mV	cable type	A 9 L item no.	A 9-100 L item no.	A 9-075 L item no.	A 9-050 L item no.	A 9-022 L item no.
Type L	5.37	LX	4428992	4426992	4425992	4423992	4501992
Type K	4.10	KCA	4428994	4426994	4425994	4423994	4501994
Type R/S	0.65	R/SCB	4428996	4426996	4425996	4423996	4501996
Type U	4.25	UX	4428993	4426993	4425993	4423993	4501993
Type B*	0.00	BC-100	4428901	4426901	4425901	4423901	4501901
Type B*	0.033	BC-200	4428902	4426902	4425902	4423902	4501902

* Not standardized compensating cable for thermocouples type B with application temperatures up to 100°C resp. 200°C.
C = compensating cables · X = extension cables