



Halogen-free Cables

SABIX® CC 625 S FRNC M

Control cable with numbered conductors and overall tinned copper shield



Marking for SABIX® CC 625 S FRNC M 62341612

SAB BRÖCKSKES · D-VIERSEN · 62341215 12 x 1.5 mm² SABIX® CC 625 S FRNC M 16 AWG/12c 62341612 AWM Style 21089 75°C 600V CSA AWM I/II A/B 80°C 600V FT1 CE

Construction:

Conductor:	bare copper strands acc. to IEC 60228, VDE 0295, class 5
Insulation:	SABIX®
Color code:	black conductors with consecutive numbers acc. to EN 50334 + VDE 0293-334, green/yellow ground from 3 conductors
Stranding:	in layers
Wrapping:	foil
Shielding:	tinned copper braiding
Jacket material:	SABIX®
Jacket color:	gray (RAL 7000)

Technical data:

Nominal voltage:	Uo/U 300/500 V
Voltage UL/CSA:	600 V
Testing voltage:	conductor/conductor: 3000 V conductor/shielding: 2000 V
Min. bending radius:	<i>fixed installation:</i> 5 x O.D. <i>free movement:</i> 10 x O.D.
Temperature range:	UL: up to +75°C CSA: up to +80°C <i>static:</i> DIN VDE: -40/+90°C <i>flexible:</i> -30/+90°C
Halogen-free:	acc. to IEC 60754-1 + VDE 0482-754-1
Burning characteristics:	no flame propagation acc. to IEC 60332-3-24 + VDE 0482-332-3-24 resp. IEC 60332-3-25 + VDE 0482-332-3-25 cat. C resp. D acc. to RoHS directive of the European Union Flame retardant and self-extinguishing acc. to IEC 60332-1-2 + VDE 0482-332-1-2
Corrosivity:	in compliance with IEC 60754-2 + VDE 0482-754-2 - no development of corrosive conflagration gases
Smoke density:	acc. to IEC 61034 + VDE 0482-1034
Flexibility:	good
Approvals:	UR AWM, CSA AWM, CE, EAC, RoHS
Absence of harmful substances:	acc. to RoHS directive of the European Union see page O/30

Outstanding features:

- low smoke halogen-free (LSHF)
 - UL recognized, CSA approved
 - no flame propagation
 - good EMC characteristics*
 - flame retardant and self-extinguishing
 - flexible
- *copper braiding should be connected circularly to optimize the EMC characteristics

item no.	no. of conductors incl. ground	nominal outer-ø inch ±5%	nominal outer-ø mm ±5%	cable weight ≈lbs/mft
▶ 20 AWG (≈ 16/32) ▪ 0.50 mm²				
62342002	2	0.224	5.7	30
62342003	3	0.236	6.0	36
62342004	4	0.252	6.4	43
62342005	5	0.276	7.0	51
62342007	7	0.299	7.6	65
62342008	8	0.350	8.9	81
62342009	9	0.370	9.4	88
62342010	10	0.378	9.6	91
62342012	12	0.386	9.8	102
62342014	14	0.421	10.7	126
62342016	16	0.441	11.2	138
62342018	18	0.472	12.0	157
62342025	25	0.543	13.8	206
62342030	30	0.591	15.0	243
62342034	34	0.642	16.3	288
62342040	40	0.693	17.6	338
62342041	41	0.693	17.6	345
62342061	61	0.795	20.2	466

item no.	no. of conductors incl. ground	nominal outer-ø inch ±5%	nominal outer-ø mm ±5%	cable weight ≈lbs/mft
▶ 19 AWG (≈ 23/32) ▪ 0.75 mm²				
62341902	2	0.244	6.2	35
62341903	3	0.256	6.5	43
62341904	4	0.276	7.0	52
62341905	5	0.307	7.8	63
62341907	7	0.331	8.4	79
62341908	8	0.386	9.8	97
62341909	9	0.425	10.8	122
62341910	10	0.433	11.0	122
62341912	12	0.445	11.3	139
62341914	14	0.472	12.0	158
62341916	16	0.496	12.6	174
62341918	18	0.520	13.2	192
62341925	25	0.642	16.3	280
62341930	30	0.661	16.8	314
62341934	34	0.717	18.2	359
62341940	40	0.776	19.7	420
62341941	41	0.776	19.7	427
62341961	61	0.902	22.9	591

item no.	no. of conductors incl. ground	nominal outer-ø inch ±5%	nominal outer-ø mm ±5%	cable weight ≈lbs/mft
▶ 18 AWG (≈ 30/32) ▪ 1.00 mm²				
62341802	2	0.252	6.4	39
62341803	3	0.268	6.8	49
62341804	4	0.287	7.3	58
62341805	5	0.315	8.0	72
62341807	7	0.350	8.9	93
62341808	8	0.398	10.1	111
62341809	9	0.441	11.2	134
62341810	10	0.449	11.4	141
62341812	12	0.469	11.9	162
62341814	14	0.488	12.4	180
62341818	18	0.547	13.9	228
62341825	25	0.665	16.9	325
62341830	30	0.697	17.7	374
62341834	34	0.752	19.1	423
62341840	40	0.811	20.6	490
62341841	41	0.811	20.6	499
62341861	61	0.945	24.0	700

Continued on next page




also available with inner jacket



Halogen-free Cables

SABIX® CC 625 S FRNC M

Control cable with numbered conductor and overall tinned copper shield



Marking for SABIX® CC 625 S FRNC M 62341612:

SAB BRÖCKSKES · D-VIERSEN · 62341215 12 x 1.5 mm² SABIX® CC 625 S FRNC M 16 AWG/12c 62341612 AWM Style 21089 75°C 600V CSA AWM I/II A/B 80°C 600V FT1 CE

item no.	no. of conductors incl. ground	nominal outer-ø		cable weight ≈lbs/mft
		inch ±5%	mm ±5%	
▶ 16 AWG (≈ 27-29/30) ▪ 1.50 mm²				
62341602	2	0.276	7.0	48
62341603	3	0.295	7.5	62
62341604	4	0.319	8.1	76
62341605	5	0.354	9.0	93
62341607	7	0.386	9.8	120
62341608	8	0.465	11.8	159
62341609	9	0.492	12.5	174
62341610	10	0.504	12.8	183
62341612	12	0.524	13.3	210
62341614	14	0.547	13.9	238
62341618	18	0.622	15.8	312
62341625	25	0.756	19.2	433
62341630	30	0.780	19.8	493
62341634	34	0.843	21.4	561
62341640	40	0.909	23.1	647
62341641	41	0.909	23.1	653
62341661	61	1.067	27.1	943

item no.	no. of conductors incl. ground	nominal outer-ø		cable weight ≈lbs/mft
		inch ±5%	mm ±5%	
▶ 14 AWG (≈ 46/30) ▪ 2.50 mm²				
62341402	2	0.327	8.3	68
62341403	3	0.354	9.0	91
62341404	4	0.382	9.7	113
62341405	5	0.433	11.0	148
62341407	7	0.476	12.1	192
62341408	8	0.555	14.1	232
62341409	9	0.598	15.2	259
62341410	10	0.618	15.7	288
62341412	12	0.646	16.4	331
62341418	18	0.760	19.3	478
62341425	25	0.921	23.4	648
▶ 12 AWG (≈ 52/28) ▪ 4.00 mm²				
62341203	3	0.417	10.6	138
62341204	4	0.453	11.5	172
62341205	5	0.504	12.8	212
62341207	7	0.555	14.1	277

item no.	no. of conductors incl. ground	nominal outer-ø		cable weight ≈lbs/mft
		inch ±5%	mm ±5%	
▶ 10 AWG (≈ 78/28) ▪ 6.00 mm²				
62341003	3	0.484	12.3	191
62341004	4	0.535	13.6	243
62341005	5	0.594	15.1	302
▶ 8 AWG (≈ 77/26) ▪ 10.00 mm²				
62340804	4	0.720	18.3	427
62340805	5	0.795	20.2	526
▶ 6 AWG (≈ 122/26) ▪ 16.00 mm²				
62340604	4	0.874	22.2	623
▶ 4 AWG (≈ 190/26) ▪ 25.00 mm²				
62340404	4	1.079	27.4	974
▶ 2 AWG (≈ 272/26) ▪ 35.00 mm²				
62340204	4	1.232	31.3	1316

Other dimensions and colors are available on request