


Metal Cable Glands

CG 350 PG

Stainless steel cord grip, SS303 or SS316

PG Thread

Impact resistant, suitable for industrial and food and beverage applications, water tight, corrosion resistant.



Technical data:

Material:	Stainless steel (AISI 303) or AISI 316L)
Clamping Insert:	Polyamide 6
Seal:	Chloroprene (CR)
O-Ring:	Neoprene (NBR)
Protection type:	IP 68 - 5 Bar; NEMA 4X
Temperature range:	
<i>permanent:</i>	-20°C to +100°C
<i>intermittent:</i>	-40°C to +150°C
Flammability:	V2 (according to UL 94)
Approvals:	cURus, cULus, DNV-GL, CE



Part Number		Thread Type	Clamping Range Ø min-max		Outer Diameter (D) inches	Wrenching Flats		Thread Diameter (TD) inches	Thread Length (TL) inches	Max. Height (H) inches	UL
SS 303	SS 316		(CR) inches	mm		Cap (SW1) inches	Body (SW2) inches				
SP3-7R	SP6-7R	PG 7	0.079 - 0.197	2.0 - 5.0	0.610	0.551	0.551	0.492	0.236	0.945	-
SP3-7RL	SP6-7RL	PG 7	0.079 - 0.197	2.0 - 5.0	0.610	0.551	0.551	0.492	0.394	0.945	-
SP3-7	SP6-7	PG 7	0.118 - 0.256	3.0 - 6.5	0.610	0.551	0.551	0.492	0.236	0.945	cURus
SP3-7L	SP6-7L	PG 7	0.118 - 0.256	3.0 - 6.5	0.610	0.551	0.551	0.492	0.394	0.945	-
SP3-9R	SP6-9R	PG 9	0.079 - 0.236	2.0 - 6.0	0.827	0.669	0.748	0.598	0.236	1.004	-
SP3-9RL	SP6-9RL	PG 9	0.079 - 0.236	2.0 - 6.0	0.827	0.669	0.748	0.598	0.394	1.004	-
SP3-9	SP6-9	PG 9	0.157 - 0.315	4.0 - 8.0	0.827	0.669	0.748	0.598	0.236	1.004	cURus
SP3-9L	SP6-9L	PG 9	0.157 - 0.315	4.0 - 8.0	0.827	0.669	0.748	0.598	0.394	1.004	-
SP3-11R	SP6-11R	PG 11	0.118 - 0.276	3.0 - 7.0	0.945	0.866	0.866	0.732	0.236	1.083	-
SP3-11RL	SP6-11RL	PG 11	0.118 - 0.276	3.0 - 7.0	0.945	0.866	0.866	0.732	0.394	1.083	-
SP3-11	SP6-11	PG 11	0.197 - 0.394	5.0 - 10.0	0.945	0.866	0.866	0.732	0.236	1.083	cURus
SP3-11L	SP6-11L	PG 11	0.197 - 0.394	5.0 - 10.0	0.945	0.866	0.866	0.732	0.394	1.083	-
SP3-13R	SP6-13R	PG 13.5	0.197 - 0.354	5.0 - 9.0	0.945	0.866	0.866	0.803	0.256	1.024	-
SP3-13RL	SP6-13RL	PG 13.5	0.197 - 0.354	5.0 - 9.0	0.945	0.866	0.866	0.803	0.394	1.024	-
SP3-13	SP6-13	PG 13.5	0.236 - 0.472	6.0 - 12.0	0.945	0.866	0.866	0.803	0.256	1.024	cULus
SP3-13L	SP6-13L	PG 13.5	0.236 - 0.472	6.0 - 12.0	0.945	0.866	0.866	0.803	0.394	1.024	-
SP3-16R	SP6-16R	PG 16	0.276 - 0.472	7.0 - 12.0	1.043	0.945	0.945	0.886	0.256	1.181	-
SP3-16RL	SP6-16RL	PG 16	0.276 - 0.472	7.0 - 12.0	1.043	0.945	0.945	0.886	0.394	1.181	-
SP3-16	SP6-16	PG 16	0.394 - 0.551	10.0 - 14.0	1.043	0.945	0.945	0.886	0.256	1.181	cULus
SP3-16L	SP6-16L	PG 16	0.394 - 0.551	10.0 - 14.0	1.043	0.945	0.945	0.886	0.394	1.181	-
SP3-21R	SP6-21R	PG 21	0.354 - 0.630	9.0 - 16.0	1.299	1.181	1.181	1.114	0.283	1.378	-
SP3-21RL	SP6-21RL	PG 21	0.354 - 0.630	9.0 - 16.0	1.299	1.181	1.181	1.114	0.472	1.378	-
SP3-21	SP6-21	PG 21	0.512 - 0.709	13.0 - 18.0	1.299	1.181	1.181	1.114	0.283	1.378	cULus
SP3-21L	SP6-21L	PG 21	0.512 - 0.709	13.0 - 18.0	1.299	1.181	1.181	1.114	0.472	1.378	-
SP3-29R	SP6-29R	PG 29	0.472 - 0.787	12.0 - 20.0	1.791	1.614	1.614	1.457	0.315	1.594	-
SP3-29RL	SP6-29RL	PG 29	0.472 - 0.787	12.0 - 20.0	1.791	1.614	1.614	1.457	0.472	1.594	-
SP3-29	SP6-29	PG 29	0.709 - 0.984	18.0 - 25.0	1.791	1.614	1.614	1.457	0.315	1.594	cULus
SP3-29L	SP6-29L	PG 29	0.709 - 0.984	18.0 - 25.0	1.791	1.614	1.614	1.457	0.472	1.594	-
SP3-36R	SP6-36R	PG 36	0.787 - 1.024	20.0 - 26.0	2.185	1.969	1.969	1.850	0.354	1.969	-
SP3-36RL	SP6-36RL	PG 36	0.787 - 1.024	20.0 - 26.0	2.185	1.969	1.969	1.850	0.551	1.969	-
SP3-36	SP6-36	PG 36	0.866 - 1.260	22.0 - 32.0	2.185	1.969	1.969	1.850	0.354	1.969	cULus
SP3-36L	SP6-36L	PG 36	0.866 - 1.260	22.0 - 32.0	2.185	1.969	1.969	1.850	0.551	1.969	-
SP3-42R	SP6-42R	PG 42	0.984 - 1.220	25.0 - 31.0	2.618	2.362	2.362	2.126	0.472	2.008	-
SP3-42RL	SP6-42RL	PG 42	0.984 - 1.220	25.0 - 31.0	2.618	2.362	2.362	2.126	0.630	2.008	-
SP3-42	SP6-42	PG 42	1.181 - 1.496	30.0 - 38.0	2.618	2.362	2.362	2.126	0.472	2.008	cULus
SP3-42L	SP6-42L	PG 42	1.181 - 1.496	30.0 - 38.0	2.618	2.362	2.362	2.126	0.630	2.008	-
SP3-48R	SP6-48R	PG 48	1.142 - 1.378	29.0 - 35.0	2.835	2.559	2.559	2.335	0.551	2.146	-
SP3-48RL	SP6-48RL	PG 48	1.142 - 1.378	29.0 - 35.0	2.835	2.559	2.559	2.335	0.709	2.146	-

Stainless steel locknut available upon request

