


Cord Grips & Accessories

CG 350 NPT

Stainless steel cord grip, SS303 or SS316

NPT Thread

Impact resistant, suitable for industrial and food and beverage applications, water tight, corrosion resistant.



Technical data:

Material:	Stainless steel (AISI 303) or AISI 316L)
Clamping Insert:	Polyamide 6
Seal:	Chloroprene (CR)
O-Ring:	Neoprene (NBR)
Protection type:	IP 68 - 5 Bar
Temperature range:	
<i>permanent:</i>	-20°C to +100°C
<i>intermittent:</i>	-40°C to +150°C
Flammability:	V2 (according to UL 94)
Approvals:	cURus, cULus, DNV-GL, CE



Part Number		Thread Type	Clamping Range Ø min-max (CR)		Outer Diameter (D) inches	Wrenching Flats		Thread Diameter (TD) inches	Thread Length (TL) inches	Max. Height (H) inches	UL
SS 303	SS 316		inches	mm		Cap (SW1) inches	Body (SW2) inches				
NPT											
SN3-3/8R	SN6-3/8R	NPT 3/8	0.079 - 0.236	2.0 - 6.0	0.827	0.669	0.748	0.675	0.453	1.004	-
SN3-3/8	SN6-3/8	NPT 3/8	0.157 - 0.315	4.0 - 8.0	0.827	0.669	0.748	0.675	0.453	1.004	cURus
SN3-3/8RC	SN6-3/8RC	NPT 3/8	0.118 - 0.276	3.0 - 7.0	0.945	0.866	0.787	0.675	0.453	1.240	-
SN3-3/8C	SN6-3/8C	NPT 3/8	0.197 - 0.394	5.0 - 10.0	0.945	0.866	0.787	0.675	0.453	1.240	cURus
SN3-1/2R	SN6-1/2R	NPT 1/2	0.197 - 0.354	5.0 - 9.0	1.181	0.866	1.063	0.840	0.512	1.220	-
SN3-1/2	SN6-1/2	NPT 1/2	0.236 - 0.472	6.0 - 12.0	1.181	0.866	1.063	0.840	0.512	1.220	cULus
SN3-1/2RC	SN6-1/2RC	NPT 1/2	0.276 - 0.472	7.0 - 12.0	1.043	0.945	0.945	0.840	0.512	1.181	-
SN3-1/2C	SN6-1/2C	NPT 1/2	0.394 - 0.551	10.0 - 14.0	1.043	0.945	0.945	0.840	0.512	1.181	cULus
SN3-3/4R	SN6-3/4R	NPT 3/4	0.354 - 0.630	9.0 - 16.0	1.299	1.181	1.181	1.050	0.512	1.496	-
SN3-3/4	SN6-3/4	NPT 3/4	0.512 - 0.709	13.0 - 18.0	1.299	1.181	1.181	1.050	0.512	1.496	cULus
SN3-1R	SN6-1R	NPT 1	0.472 - 0.787	12.0 - 20.0	1.791	1.614	1.614	1.315	0.512	1.791	-
SN3-1	SN6-1	NPT 1	0.709 - 0.984	18.0 - 25.0	1.791	1.614	1.614	1.315	0.512	1.791	cULus
SN3-1 1/4	SN6-1 1/4	NPT 1 1/4	0.866 - 1.260	22.0 - 32.0	2.185	1.969	1.969	1.660	1.008	2.008	-
SN3-1 1/2	SN6-1 1/2	NPT 1 1/2	1.181 - 1.496	30.0 - 38.0	2.618	2.362	2.362	1.900	1.024	1.969	-
SN3-2	SN6-2	NPT 2	1.339 - 1.732	34.0 - 44.0	2.835	2.559	2.559	2.375	1.063	2.165	-

Stainless steel locknut available upon request

Locknuts need to be purchased separately, see page N/27