


Halogen-free Cables

SABIX® R 600 FRNC

SABIX® Rail - Control cable with numbered conductors



Marking for SABIX® R 600 FRNC 66001215:

SAB BRÖCKSKES · D-VIERSEN · SABIX® R 600 FRNC 12 x 1.5 mm² CE

Construction:

Conductor:	bare copper strands acc. to IEC 60228, VDE 0295, class 5
Insulation:	special SABIX®
Color code:	black conductors with consecutive numbers acc. to EN 50334 + VDE 0293-334, green/yellow ground from 3 conductors
Stranding:	in layers
Jacket material:	special SABIX®
Jacket color:	gray (RAL 7000)

Outstanding features:

- low smoke halogen-free (LSHF)
- no flame propagation
- flame retardant and self-extinguishing
- fulfills fire protection requirements R15 (EL1A)
acc. to EN 45545-2 for hazard levels HL1-3

Technical data:

Nominal voltage:	Uo/U 300/500 V
Testing voltage:	conductor/conductor: 3000 V
Min. bending radius:	<i>fixed installation:</i> 4 x O.D. <i>free movement:</i> 6 x O.D.
Temperature range:	<i>static:</i> -40/+90°C <i>flexible:</i> -30/+90°C
Halogen-free:	acc. to EN 50306-1 + EN 50264-1 are fulfilled. Development of HCl is < 0.5% acc. to IEC 60754-1. pH-value is > 4.3 acc. to IEC 60754-2. Conductivity is < 10.0 µS/mm acc. to IEC 60754-2. Fluoric content < 0.1% acc. to IEC 60684-2
Burning characteristics:	No flame propagation acc. to IEC 60332-3-24, IEC 60332-3-25 + EN 50305 section 9.1.2. Flame retardant and self-extinguishing acc. to IEC 60332-1-2 + VDE 0482-332-1-2 Flame retardant acc. to ISO 6722 (UN/ECE R118)
Toxicity:	acc. to EN 50305 + VDE 0260-305
Smoke density:	acc. to IEC 61034 + VDE 0482-1034
Flexibility:	good
Approvals:	CE, EAC, RoHS
Absence of harmful substances:	acc. to RoHS directive of the European Union see page O/30

item no.	no. of conductors incl. ground	nominal outer-ø inch ±5%	mm ±5%	cable weight ≈lbs/mft
► 20 AWG (≈ 16/32) • 0.50 mm²				
66000205	2	0.189	4.8	22
66000305	3	0.201	5.1	26
66000405	4	0.217	5.5	31
66000505	5	0.244	6.2	38
66000705	7	0.264	6.7	46
66001005	10	0.339	8.6	65
66001205	12	0.358	9.1	74
66001805	18	0.421	10.7	114
66002505	25	0.508	12.9	148
66003205	32	0.551	14.0	193
66004205	42	0.618	15.7	245
66006105	61	0.728	18.5	343
► 19 AWG (≈ 23/32) • 0.75 mm²				
66000207	2	0.213	5.4	30
66000307	3	0.224	5.7	34
66000407	4	0.252	6.4	42
66000507	5	0.276	7.0	52
66000707	7	0.307	7.8	65
66001007	10	0.394	10.0	97
66001207	12	0.413	10.5	110
66001807	18	0.488	12.4	155
66002507	25	0.594	15.1	212
66003207	32	0.646	16.4	261
66004207	42	0.724	18.4	346
66006107	61	0.850	21.6	484
► 18 AWG (≈ 30/32) • 1.00 mm²				
66000210	2	0.220	5.6	34
66000310	3	0.240	6.1	42
66000410	4	0.260	6.6	51
66000510	5	0.295	7.5	63
66000710	7	0.319	8.1	79

item no.	no. of conductors incl. ground	nominal outer-ø inch ±5%	mm ±5%	cable weight ≈lbs/mft
► 18 AWG (≈ 30/32) • 1.00 mm²				
66001010	10	0.417	10.6	116
66001210	12	0.429	10.9	132
66001810	18	0.508	12.9	188
66002510	25	0.618	15.7	256
66003210	32	0.673	17.1	327
66004210	42	0.764	19.4	414
66006110	61	0.894	22.7	587
► 16 AWG (≈ 27-29/30) • 1.50 mm²				
66000215	2	0.252	6.4	46
66000315	3	0.268	6.8	54
66000415	4	0.299	7.6	67
66000515	5	0.327	8.3	83
66000715	7	0.362	9.2	114
66001015	10	0.472	12.0	154
66001215	12	0.488	12.4	177
66001815	18	0.583	14.8	194
66002515	25	0.709	18.0	361
66003215	32	0.768	19.5	444
66004215	42	0.866	22.0	583
66006115	61	1.016	25.8	818
► 14 AWG (≈ 46/30) • 2.50 mm²				
66000225	2	0.307	7.8	71
66000325	3	0.350	8.9	85
66000425	4	0.362	9.2	104
66000525	5	0.398	10.1	134
66000725	7	0.441	11.2	169
66001025	10	0.583	14.8	243
66001225	12	0.602	15.3	280
66001825	18	0.717	18.2	413
66002525	25	0.878	22.3	562

item no.	no. of conductors incl. ground	nominal outer-ø inch ±5%	mm ±5%	cable weight ≈lbs/mft
► 12 AWG (≈ 52/28) • 4.00 mm²				
66000340	3	0.382	9.7	124
66000440	4	0.425	10.8	157
66000540	5	0.476	12.1	195
66000740	7	0.528	13.4	252
► 10 AWG (≈ 78/28) • 6.00 mm²				
66000360	3	0.449	11.4	181
66000460	4	0.500	12.7	226
66000560	5	0.559	14.2	279
66000760	7	0.618	15.7	366
► 8 AWG (≈ 77/26) • 10.00 mm²				
66000461	4	0.657	16.7	389
66000561	5	0.732	18.6	497
66000761	7	0.815	20.7	645
► 6 AWG (≈ 122/26) • 16.00 mm²				
66000462	4	0.811	20.6	596
66000562	5	0.906	23.0	742
66000762	7	1.004	25.5	971
► 4 AWG (≈ 190/26) • 25.00 mm²				
66000463	4	0.980	24.9	933
66000563	5	1.106	28.1	1176
► 2 AWG (≈ 272/26) • 35.00 mm²				
66000464	4	1.134	28.8	1295
66000564	5	1.280	32.5	1621

Other dimensions and colors are available on request